

Courtesy — Norm & Bev Voelzow



Voelzow & Company, Inc.

4804 Lawyers Rd E • Wingate, NC 28174
 704-233-9222 • Fax 704-233-9211
 E-mail: nvoelzow@perigee.net
 Web: www.LaserAlignment.net



TOLERANCES FOR SHAFT ALIGNMENT (±)



RPM	GAP (mils/10") 		OFFSET (mils) 		SPACER SHAFT (mils/in.)	
	Excellent	Acceptable	Excellent	Acceptable	Excellent	Acceptable
600	10.0	15.0	5.0	9.0	1.8	3.0
900	7.0	10.0	3.0	6.0	1.2	2.0
1200	5.0	8.0	2.5	4.0	0.9	1.5
1800	3.0	5.0	2.0	3.0	0.6	1.0
3600	2.0	3.0	1.0	1.5	0.3	0.5
7200	1.0	2.0	0.5	1.0	0.15	0.25

8ths
 1/8 = .125
 1/4 = .250
 3/8 = .375
 1/2 = .500
 5/8 = .625
 3/4 = .750
 7/8 = .875

Related Products:

- SS Shims
- Undercut Bolts
- Portable Jack Bolt Kits
- Heavy Lifting Devices
- and more ...

All RPM: Maximum Soft Foot Reading 2.0 mils. (1 mil = .001")
 Note: Use OEM or in-house tolerances if available.

Copyright 2003 by LUDECA, INC., Miami, FL